



SSM 整合之 applicationContext.xml 文件配置

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<beans xmlns="http://www.springframework.org/schema/beans"
```

```
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```
    xmlns:context="http://www.springframework.org/schema/context"
```

```
    xmlns:aop="http://www.springframework.org/schema/aop"
```

```
    xmlns:tx="http://www.springframework.org/schema/tx"
```

```
    xmlns:mvc="http://www.springframework.org/schema/mvc"
```

```
    xsi:schemaLocation="http://www.springframework.org/schema/beans
```

```
        http://www.springframework.org/schema/beans/spring-beans.xsd
```

```
        http://www.springframework.org/schema/context
```

```
        http://www.springframework.org/schema/context/spring-context.xs
```

d

```
        http://www.springframework.org/schema/aop
```

```
        http://www.springframework.org/schema/aop/spring-aop.xsd
```

```
        http://www.springframework.org/schema/tx
```

```
        http://www.springframework.org/schema/tx/spring-tx.xsd
```

```
        http://www.springframework.org/schema/mvc
```

```
        http://www.springframework.org/schema/mvc/spring-mvc.xsd">
```

```
<!-- 扫描注解-->
```



```
<context:component-scan base-package="ssm_service.Impl"></context:comp
onent-scan>

<!--扫描软编码文件-->

<context:property-placeholder location="classpath:db.properties"></context:
property-placeholder>

<!--配置 dataSource-->

<bean id="dataSource" class="org.springframework.jdbc.datasource.DriverMa
nagerDataSource">

    <property name="driverClassName" value="{jdbc.driver}"></property>
    <property name="url" value="{jdbc.url}"></property>
    <property name="username" value="{jdbc.username}"></property>
    <property name="password" value="{jdbc.password}"></property>
</bean>

<bean id="factory" class="org.mybatis.spring.SqlSessionFactoryBean">
    <property name="dataSource" ref="dataSource"></property>
    <property name="typeAliasesPackage" value="ssm_domain"></property
>

<!-- 传入 PageHelper 的插件 -->

<property name="plugins">
    <array>
        <!-- 传入插件的对象 -->
        <bean class="com.github.pagehelper.PageInterceptor">
```



```
<property name="properties">
    <props>
        <prop key="helperDialect">mysql</prop>
        <prop key="reasonable">>true</prop>
    </props>
</property>
</bean>
</array>
</property>
</bean>
<!-- -->
<bean class="org.mybatis.spring.mapper.MapperScannerConfigurer">
    <property name="basePackage" value="ssm_dao"> </property>
    <property name="sqlSessionFactoryBeanName" value="factory"> </prope
rty>
</bean>
<!--配置 aop 切点-->
<aop:config>
    <aop:pointcut id="mypoint" expression="execution(* ssm_service.Impl.*.*
(..))"/>
    <aop:advisor advice-ref="txAdvice" pointcut-ref="mypoint"> </aop:advis
or>
```



```
</aop:config>

<bean id="transactionManager" class="org.springframework.jdbc.datasource.
DataSourceTransactionManager">
    <property name="dataSource" ref="dataSource"></property>
</bean>

<tx:advice id="txAdvice" transaction-manager="transactionManager">
    <tx:attributes>
        <tx:method name="ins*" ></tx:method>
        <tx:method name="upd*" ></tx:method>
        <tx:method name="del*" ></tx:method>
        <tx:method name="*" read-only="true"></tx:method>
    </tx:attributes>
</tx:advice>

</beans>
```