

hostnamectl 命令简单介绍

在CentOS7中有三种定义的主机名：

静态的（static）、瞬态的（transient）、和灵活的（pretty）。

1、hostnamectl --help 或者 hostnamectl -h

```
1 hostnamectl [OPTIONS...] COMMAND ...
2
3 Query or change system hostname.
4
5 -h --help          Show this help
6 --version         Show package version
7 --no-ask-password Do not prompt for password
8 -H --host=[USER@]HOST Operate on remote host
9 -M --machine=CONTAINER Operate on local container
10 --transient       Only set transient hostname
11 --static          Only set static hostname
12 --pretty         Only set pretty hostname
13
14 Commands:
15 status           Show current hostname settings      显示当前主机配置
16 set-hostname NAME Set system hostname          设置主机名称
17 set-icon-name NAME Set icon name for host      设置主机图标名称
18 set-chassis NAME Set chassis type for host     设置主机底盘类型
19 set-deployment NAME Set deployment environment for host 设置主机部署环境
20 set-location NAME Set location for host
```

2、hostnamectl 或者 hostnamectl status

```
1 Static hostname (主机名称): liangkk
2 Icon name (图标名称): computer-vm
3 Chassis (底盘类型): vm
4 Machine ID (机器ID): 963c2c41b0833f7b063dddac6b2e486
5 Boot ID (引导ID): 83dee24a02896b5a73986b1913f61f7
6 Virtualization (虚拟化): kvm
7 Operating System (操作系统): CentOS Linux 7 (Core)
8 CPE OS Name (操作系统): cpe:/o:centos:centos:7
9 Kernel (内核): Linux 3.10.0-514.26.2.el7.x86_64
10 Architecture (架构): x86-64
```